

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

Listing of Claims

1 1 (Currently Amended): A method of providing differentiated services for IP
2 packets transported on an asynchronous transfer mode (ATM) backbone, said method
3 comprising:

4 provisioning a first switched virtual circuit (SVC) and a second SVC on said ATM
5 backbone, each of said first SVC and said second SVC being provisioned as a unicast
6 point-to-point virtual circuit terminating between same end devices;

7 receiving an IP packet;

8 determining whether to send said IP packet on said first SVC or said second SVC
9 according to services desired to be provided for said IP packet; and

10 sending said IP packet on the determined one of said first SVC or said second SVC.

1 2 (Currently Amended): The method of claim 1, wherein said determining comprises
2 examining a header of said IP packet and wherein said services desired for said IP packet
3 being based on said header.

1 3 (Currently Amended): The method of claim 2, wherein said determining further
2 comprises maintaining a table indicating a specific one of said first SVC and said second
3 SVC on which to send IP packets having a specific precedence value in a type of service
4 (TOS) field in said header, wherein said IP packet is sent on either said first SVC or said
5 second SVC according to the data stored in said table.

1 4 (Original): The method of claim 3, wherein said table indicates that a plurality of
2 precedence values are to be mapped to the same SVC.

1 5 (Original): The method of claim 3, wherein said provisioning comprises initiating
2 a set up request from a first router to a second router to set up said first SVC, wherein said
3 first router and said second router interface directly with said ATM backbone, wherein said

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

4 set up request is sent only after reception of a first IP packet to be sent on said first SVC,
5 wherein said first SVC is provisioned between said first router and said second router.

1 6 (Original): The method of claim 5, wherein said second router also sends on said
2 first SVC the IP packets having the same precedence value as said first IP packet.

1 7 (Currently Amended): The method of claim 6, further comprising sending a
2 precedence data from said first router to said second router, wherein said precedence data
3 indicates that the precedence value of said first IP packet is to be associated with said first
4 SVC such that said second router can send packets with the same precedence value vale
5 on said first SVC.

1 8 (Currently Amended): The method of claim 7, wherein said precedence data is
2 contained in a signaling set up message representing said set up request.

1 9 (Original): The method of claim 8, wherein said precedence data is encoded in a
2 broadband higher layer information (BHLLI) information element (IE) contained in said
3 signaling set up message.

1 10 (Original): The method of claim 9, wherein each of said first router and said
2 second router comprises an edge router.

1 11 (Currently Amended): The method of claim 5 2, wherein said table stores an IP
2 address, a network service access point (NSAP) of said second router, a precedence value
3 contained in said header, and a SVC identifier in each row.

12 (Withdrawn): A method of providing differentiated services for IP packets
transported on an asynchronous transfer mode (ATM) backbone, said method being
performed in a receiving router, said method comprising:

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

receiving in said receiving router a set up request from another router, wherein said set up request requests setting up of a switched virtual circuit (SVC), said another router sending all IP packets having a specific precedence value on said SVC;

configuring said receiving router to terminate said SVC in said receiving router;

sending an acknowledgment confirming setting up of said SVC; and

sending a plurality of IP packets having the same precedence value as said specific precedence value on said SVC.

13 (Withdrawn): The method of claim 12, further comprising receiving a precedence data from said another router data indicating that said specific precedence value is associated with said SVC.

14 (Withdrawn): The method of claim 13, wherein said precedence data is contained in a Signaling set up message representing said set up request.

15 (Withdrawn): The method of claim 14, wherein said precedence data is encoded in a broadband higher layer information (BHLLI) information element (IE) contained in said Signaling set up message.

1 16 (Currently Amended): A router for providing differentiated services for IP
2 packets transported on an asynchronous transfer mode (ATM) backbone, said router
3 comprising:

4 means for provisioning a first switched virtual circuit (SVC) and a second SVC on
5 said ATM backbone, each of said first SVC and said second SVC being provisioned as a
6 unicast point-to-point virtual circuit terminating between same end devices;

7 means for receiving an IP packet;

8 means for determining whether to send said IP packet on said first SVC or said
9 second SVC according to services desired to be provided for said IP packet; and

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

10 means for sending said IP packet on the determined one of said first SVC or said
11 second SVC.

1 17 (Currently Amended): The router of claim 16, wherein said means for
2 determining examines a header of said IP packet to determine whether to send said IP
3 packet on said first SVC or said second SVC and wherein said services desired for said IP
4 packet being based on said header.

1 18 (Currently Amended): The router of claim 17, wherein said means for
2 determining further maintains a table indicating a specific one of said first SVC and said
3 second SVC on which to send IP packets having a specific precedence value in a type of
4 service (TOS) field in said header, wherein said IP packet is sent on either said first SVC
5 or said second SVC according to the data stored in said table.

1 19 (Original): The router of claim 18, wherein said table indicates that a plurality
2 of precedence values are to be mapped to the same SVC.

1 20 (Currently Amended): The router of claim 18, wherein said means for
2 provisioning initiates a set up request to another router to set up said first SVC, wherein
3 said set up request is sent only after reception of a first IP packet to be sent on said first
4 SVC, wherein said first SVC is provisioned to terminate at said ~~second~~ another router.

1 21 (Original): The router of claim 20, wherein said another router also sends on said
2 first SVC the IP packets having the same precedence value as said first IP packet.

1 22 (Currently Amended): The router of claim 21, further comprising means for
2 sending a precedence data to said another router, wherein said precedence data indicates
3 that the precedence value of said first IP packet is to be associated with said first SVC such
4 that another router can send packets with the same precedence value ~~val~~ on said first SVC.

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

1 23 (Currently Amended): The router of claim 22, wherein said precedence data is
2 encoded in a broadband higher layer information (BHLD) information element (IE)
3 contained in a said Signaling set up message.

24 (Withdrawn): A receiving router for providing differentiated services for IP packets transported on an asynchronous transfer mode (ATM) backbone, said receiving router comprising:

means for receiving in said receiving router a set up request from another router, wherein said set up request requests setting up of a switched virtual circuit (SVC), said another router sending all IP packets having a specific precedence value on said SVC;

means for configuring said receiving router to terminate said SVC in said receiving router;

means for sending an acknowledgment confirming setting up of said SVC; and

means for sending a plurality of IP packets having the same precedence value as said specific precedence value on said SVC.

25 (Withdrawn): The receiving router of claim 24, further comprising means for receiving a precedence data from said another router data indicating that said specific precedence value is associated with said SVC.

26 (Withdrawn): The receiving router of claim 25, wherein said precedence data is encoded in a broadband higher layer information (BHLD) information element (IE) contained in a signaling set up message.

1 27 (Currently Amended): A computer readable medium carrying one or more
2 sequences of instructions for causing a router to provide differentiated service to IP
3 packets, wherein execution of said one or more sequences of instructions by one or more
4 processors contained in said router causes said one or more processors to perform the

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

actions of:

provisioning a first switched virtual circuit (SVC) and a second SVC on said ATM backbone, each of said first SVC and said second SVC being provisioned as a unicast point-to-point virtual circuit terminating between same end devices;

receiving an IP packet;

determining whether to send said IP packet on said first SVC or said second SVC according to services desired to be provided for said IP packet; and

sending said IP packet on the determined one of said first SVC or said second SVC.

28 (Currently Amended): The computer readable medium of claim 27, wherein said determining comprises examining a header of said IP packet and wherein said services desired for said IP packet being based on said header.

29 (Currently Amended): The computer readable medium of claim 28, wherein said determining further comprises maintaining a table indicating a specific one of said first SVC and said second SVC on which to send IP packets having a specific precedence value in a type of service (TOS) field in said header, wherein said IP packet is sent on either said first SVC or said second SVC according to the data stored in said table.

30 (Original): The computer readable medium of claim 29, wherein said table indicates that a plurality of precedence values are to be mapped to the same SVC.

31 (Original): The computer readable medium of claim 29, wherein said provisioning comprises initiating a set up request to another router to set up said first SVC, wherein said first router and said another router interface directly with said ATM backbone, wherein said set up request is sent only after reception of a first IP packet to be sent on said first SVC, wherein said first SVC is provisioned between said first router and said another router.

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

1 32 (Original): The computer readable medium of claim 31, wherein said another
2 router also sends on said first SVC the IP packets having the same precedence value as said
3 first IP packet.

1 33 (Currently Amended): The computer readable medium of claim 32, further
2 comprising sending a precedence data to said another router, wherein said precedence data
3 indicates that the precedence value of said first IP packet is to be associated with said first
4 SVC such that another router can send packets with the same precedence value ~~vale~~ on said
5 first SVC.

1 34 (Original): The computer readable medium of claim 33, wherein said precedence
2 data is encoded in a broadband higher layer information (BHLLI) information element (IE)
3 contained in a signaling set up message.

1 35 (Currently Amended): The computer readable medium of claim 33, wherein said
2 table stores an IP address, a network service access point (NSAP) of said second router,
3 a precedence value contained in said header, and a SVC identifier in each row.

36 (Withdrawn): A computer readable medium carrying one or more sequences of instructions for causing a router to provide differentiated service to IP packets transported on an asynchronous transfer mode (ATM) backbone, wherein execution of said one or more sequences of instructions by one or more processors contained in said router causes said one or more processors to perform the actions of:

receiving in said receiving router a set up request from another router, wherein said set up request requests setting up of a switched virtual circuit (SVC), said another router sending all IP packets having a specific precedence value on said SVC;

configuring said receiving router to terminate said SVC in said receiving router;

sending an acknowledgment confirming setting up of said SVC; and

sending a plurality of IP packets having the same precedence value as said specific

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

precedence value on said SVC.

37 (Withdrawn): The computer readable medium of claim 36, further comprising receiving a precedence data from said another router data indicating that said specific precedence value is associated with said SVC.

38 (Withdrawn): The computer readable medium of claim 37, wherein said precedence data is encoded in a broadband higher layer information (BHLD) information element (IE) contained in a signaling set up message.

1 39 (Currently Amended): A router for providing differentiated services for IP
2 packets transported on an asynchronous transfer mode (ATM) backbone, said router
3 comprising:

4 an inbound interface receiving an IP packet;

5 a memory storing an SVC table indicating that a first switched virtual circuit (SVC)
6 and a second SVC are provisioned on said ATM backbone, each of said first SVC and said
7 second SVC being provisioned as a unicast point-to-point virtual circuit terminating
8 between same end devices;

9 an encapsulator determining whether to send said IP packet on said first SVC or
10 said second SVC according to services desired to be provided for said IP packet, said
11 encapsulator generating a plurality of cells designed for transmission on the determined one
12 of said first SVC or said second SVC; and

13 an output interface sending said plurality of cells on said ATM backbone.

1 40 (Currently Amended): The router of claim 39, wherein said ATM encapsulator
2 examines a header of said IP packet to determine whether to send said IP packet on said
3 first SVC or said second SVC and wherein said services desired for said IP packet being
4 based on said header.

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

1 41 (Currently Amended): The router of claim 40, wherein said SVC table indicates
2 a specific one of said first SVC and said second SVC on which to send IP packets having
3 a specific precedence value in a type of service (TOS) field in said header, wherein said
4 IP packet is sent according to the data stored in said table.

1 42 (Original): The router of claim 41, wherein said table indicates that a plurality
2 of precedence values are to be mapped to the same SVC.

1 43 (Currently Amended): The router of claim 42, further comprising a signaling
2 block for initiating a set up request to another router to set up said first SVC, wherein said
3 set up request is sent only after reception of a first IP packet to be sent on said first SVC,
4 wherein said first SVC is provisioned to terminate at said another ~~second~~ router.

1 44 (Original): The router of claim 43, wherein said another router also sends on said
2 first SVC the IP packets having the same precedence value as said first IP packet.

1 45 (Currently Amended): The router of claim 44, wherein said signaling block sends
2 a precedence data to said another router, wherein said precedence data indicates that the
3 precedence value of said first IP packet is to be associated with said first SVC such that
4 another router can send packets with the same precedence value ~~vale~~ on said first SVC.

1 46 (Original): The router of claim 45, wherein said precedence data is encoded in
2 a broadband higher layer information (BHLLI) information element (IE) contained in a
3 signaling set up message.

1 47 (Currently Amended): The router of claim 41, wherein said SVC table stores a
2 network service access point (NSAP) address and IP address of an edge router at the next
3 hop associated with each SVC, wherein said encapsulator sending as a key to said table a
4 IP address of an edge router at the next hop and a precedence value in each received IP

Reply to Office Action of May 11, 2005
Amendment Dated: August 11, 2005

Appl. No.: 09/904,593
Attorney Docket No.: CSCO-008/4339

5 packet to determine whether to send said IP packet on said first SVC or said second SVC.

48 (Withdrawn): A receiving router for providing differentiated services for IP packets transported on an asynchronous transfer mode (ATM) backbone, said receiving router comprising:

an input interface receiving a set up request from another router, wherein said set up request requests setting up of a switched virtual circuit (SVC), said another router sending all IP packets having a specific precedence value on said SVC;

a memory storing information indicative of SVCs provisioned terminating in said receiving router;

a signaling block configuring said memory to terminate said SVC in response to receiving said set up request, said signaling block sending an acknowledgment confirming setting up of said SVC;

an encapsulator generating a plurality of ATM cells designed for transmission on said SVC, said ATM cells containing an IP packet having the same precedence value as said specific precedence value; and

an output interface sending said plurality of cells on said SVC.

49 (Withdrawn): The receiving router of claim 48, wherein said signaling block receives a precedence data from said another router data indicating that said specific precedence value is associated with said SVC.

50 (Withdrawn): The receiving router of claim 49, wherein said precedence data is contained in a signaling set up message representing said set up request.

51 (Withdrawn): The receiving router of claim 50, wherein said precedence data is encoded in a broadband higher layer information (BHLL) information element (IE) contained in said signaling set up message.